

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE

○	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
△	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
○	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1

A = 16 STANDARD CONTACTS L = 3
 B = 16 STANDARD CONTACTS L = 3
 C = 16 STANDARD CONTACTS L = 3
 S = 48 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G1/O = CONTACT AREA LEVEL / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0002 SHT 1

C	G1/O	c1-16
B	G1/O	b1-16
A	G1/O	a1-16
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. I 2004-XXXX DRAWN N.S. 09/09/03 CHK'd G.L. 09/09/03 APPR. G.L. 09/09/03	QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE	DESIGN UNITS	DIMENSIONS:		SHT	REV
	MAJOR	mm INCH	1:1	mm INCH	mm INCH	mm INCH	1	
	CRITICAL	mm INCH						
		mm INCH						
DESCRIPTION	THIRD ANGLE PROJECTION	DRAWN BY & DATE	TITLE:		MATERIAL NO.		DRAWING NO.	
		N.S. 18/02/02	48 POS MALE CONNECTOR		85003-0701		SD-85003-0701	
		CHECKED BY & DATE	ACCORDING DIN 41612 STYLE C/2				SHEET NO.	
		G.L. 18/02/02	CONTACTS ARRANGEMENT				1 OF 1	
		APPROVED BY & DATE	MOLEX INCORPORATED				SIZE	
		G.L. 18/02/02					D	
		CAD FILENAME	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.					
		S850030701.S01						

24-border.DGN REV 4 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 96/06/12 LEVEL 6