



PANEL CUT-OUT

NOTES:
 Material :
 1. Insulator: PBT With GF30% UL94V-0
 2. Terminal: COPPER ALLOY TIN PLATING
 Electrical:
 1. Rating: 15A 250V~(UL.CUL)
 10A 250V~
 (CCC, VDE, SEMKO, NEMKO, FIMKO, DEMKO, SAA, KC)
 2. Electric Strength : AC 2000V For 1 Minute
 3. Insulation Resistance: 100MΩ, AT500V/DC
 Approval:

- RU UL
- RU CUL
- VDE
- SEMKO
- NEMKO
- DEMKO
- FIMKO
- CCC
- KC

RoHS compliant

Scale	1:1												
TOLERANCE													
0-10	±0.1												
10-30	±0.3												
30-100	±0.5												
DIM TOL													
UNIT	mm												
<table border="1"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> </tr> </thead> <tbody> <tr> <td>①</td> <td>Drawn</td> <td>08.07.2009</td> <td>Dean</td> </tr> <tr> <td>②</td> <td>Change of plant</td> <td>06.12.2012</td> <td>Winnie</td> </tr> </tbody> </table>		Id.	Modification	Date	Name	①	Drawn	08.07.2009	Dean	②	Change of plant	06.12.2012	Winnie
Id.	Modification	Date	Name										
①	Drawn	08.07.2009	Dean										
②	Change of plant	06.12.2012	Winnie										

ASSMANN
 WSW/ components

Customer-No.
 ASSMANN WSW-No.
A-KGS-F/T2N

Drawing-No.
ASS 0889M CO
 Replace
 rev02
 SHEET

1	2	3	4	5	6	7
H	G	F	E	D	C	B
1	2	3	4	5	6	7
H	G	F	E	D	C	B