



REV.	DESCRIPTION	DATE	APPROVED
F	Corrected Board Thickness	04/01/14	J. C.
G	Engineering Release	04/01/14	J. C.
H	Removed BOM	08/09/16	J. C.



ORDERING INFORMATION
L24-ZXXXXK
CORRELATED COLOR TEMPERATURE
IN KELVIN

Part Number	LED P/N	Color	CCT (K)	Typical Luminous Flux (lm)	Philips Lumileds P/N Reference
L24-Z2700K	BDL-1509	Warm White	2700	100	LXZ1-2780-5
L24-Z3000K	BDL-1510	Warm White	3000	110	LXZ1-3080-5
L24-Z4000K	BDL-1511	Neutral White	4000	120	LXZ1-4070
L24-Z5000K	BDL-1512	Neutral White	5000	130	LXZ1-5070
L24-Z5700K	BDL-1513	Cool White	5700	140	LXZ1-5770

STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED)		 4 THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974	
DECIMALS	ANGULAR		
.X ± .1	X° ± 1°		TITLE: L24 Starboard Light Engine
.XX ± .02			DESIGNED: B. Oliver
.XXX ± .010		CHECKED: J. Chiang	DATE: 11/07/13
		PART NO: L24-ZXXXXK	REVISION: H
		CAGE CODE : 32559	SHEET # 1 OF 1
CAD GENERATED DOCUMENT. DO NOT MEASURE DRAWING.			