



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4 X:XX=±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. RATING: 7A@125V, 4A@250 VULCUL, & VDE APPROVED
  5. CONTACT MATERIAL: Terminals, Copper Alloy W/Silver plate, Contacts, Copper Alloy W/Tin Oxide
  6. CONTACT RESISTANCE: 100mΩ—ohms TYP. MAX Initial
  7. DIELECTRIC STRENGTH: 1500V for 1min 3000V between poles
  8. ELECTRICAL LIFE: 6,000 Cycles
  9. OPERATING FORCE: 550±150gf TYP.
  10. TRAVEL: FULL:5.5, LOCK:4.0
  11. ▲ DENOTES CRITICAL PARAMETER.

**E-SWITCH®**

A		13307	RELEASED FOR PRODUCTION	7/21/03	AR	TITLE	
REV.	ECN No.		DESCRIPTION	DATE	CHKD	P227EE1A20A	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED							
SCALE		1.5:1	DATE	7/21/03	DR	DWG	P030127
REV		A		AR		P030127	