

Contact insert module - HC-M-03-PN-M-F - 1417433


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert module, Number of positions: 3, Socket/pin, Application: Pneumatics, for internal hose diameter of 1.6 / 3 / 4 mm

RoHS

Key Commercial Data

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	 4 055626 112947
GTIN	4055626112947

Technical data

Dimensions

Height	27.2 mm
Width	34.1 mm
Length	14.6 mm

Electrical characteristics

Note	For HEAVYCON ADVANCE housing type B6 to B24 and HEAVYCON housing type B6 to B48. HEAVYCON HC-M-B...-MF... module carrier frame required, HC-M-PN... pneumatic pins and sockets are not supplied as standard.
Connection profile	3

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

Mechanical characteristics

Internal diameter of pressure hose connection	1.6 mm
	3 mm
	4 mm
Insertion/withdrawal cycles	≥ 500

Contact insert module - HC-M-03-PN-M-F - 1417433

Technical data

General

Color	light gray
Number of module slots	1
Flammability rating according to UL 94	V0
Assembly instructions	Use of HC-CST-MOD (1636127) coding pins and HC-CBU-MOD (1636130) coding sockets has been prescribed. When connecting the hoses, the min. bending radii should be observed
Connection	<ul style="list-style-type: none"> - Snap the pneumatic contact and module together. Insert the contact into the module from the front - Place the modules assembled with the contacts in the module carrier frame. - The pneumatic tubes are pushed onto the pneumatic contact from the back of the module. The medium-sized module slots and sleeves/coupling housing with straight cable outlet direction are recommended.

Material data


Contact carrier material	PC
--------------------------	----

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Drawings

Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

Contact insert module - HC-M-03-PN-M-F - 1417433

Approvals

EAC



7500651.22.01.00246

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>