

Specification Sheet

Part Number: 155-46302



Oval Stud Mount Cable Tie, Designed for 6.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

| | |
|--------------------------------|---|
| Article Number | 155-46302 |
| Type | T50SOSSB6HE |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Oval mount design pushes on easy by hand without the need for tools.• Design provides low insertion and high extraction force. |
| Quantity Per | bag |
| Product Description | The special oval shape provides for an approximate .24" (6.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables |
| Short Description | Oval Stud Mount Cable Tie, Designed for 6.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg |

Global Part Name

T50SOSSB6HE-PA66HS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

170

Length L (Imperial)

6.0

Length L (Metric)

160.0

Fixation Method

Weld Stud Fixing

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.19

Width W (Metric)

4.7

Bundle Diameter Min (Imperial)

0.04

Bundle Diameter Min (Metric)

1.0

Bundle Diameter Max (Imperial)

1.4

Bundle Diameter Max (Metric)

35.0

Thickness T (Imperial)

0.05

| | |
|---------------------------------------|--|
| Thickness T (Metric) | 1.35 |
| Stud Length Min (Metric) | 16.0 |
| Stud Diameter (Metric) | 6.0 mm |
| Stud Diameter (Imperial) | 0.24 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909987 |
| Content Unit(BMEcat) | pcs. |
| Weight (Metric) | 2.37 |

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)