


# Printed-circuit board connector - MCV 0,5/ 7-G-2,5 BK - 1909582

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB headers, nominal current: 4 A, number of positions: 7, pitch: 2.5 mm, color: black, contact surface: Tin, mounting: Wave soldering




The figure shows a 10-position version of the product

## Why buy this product

- Well-known mounting principle allows worldwide use
- Vertical connection enables multi-row arrangement on the PCB



## Key Commercial Data

Packing unit	50 STK
GTIN	 4 017918 450250
GTIN	4017918450250

## Technical data

### Dimensions

Pitch	2.5 mm
Dimension a	15 mm
Constructional height	11 mm
Length of the solder pin	3.5 mm
Pin dimensions	0.8 x 0.8 mm

### General

Range of articles	MCV 0,5/...-G
Rated voltage (III/3)	80 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	4 A
Color	black
Number of positions	7

# Printed-circuit board connector - MCV 0,5/ 7-G-2,5 BK - 1909582

## Technical data

### Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals


### Approvals


#### Approvals

VDE Gutachten mit Fertigungsüberwachung / IECEE CB Scheme / CCA / EAC / cULus Recognized


#### Ex Approvals

### Approval details

VDE Gutachten mit Fertigungsüberwachung		<a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a>	40013394
Nominal voltage UN	80 V		
Nominal current IN	4 A		


IECEE CB Scheme		<a href="http://www.iecee.org/">http://www.iecee.org/</a>	DE1-56068-B1B2
Nominal voltage UN	80 V		
Nominal current IN	4 A		

CCA	CCA/ DE1 34250		
Nominal voltage UN	80 V		
Nominal current IN	4 A		

EAC		B.01742	
-----	---	---------	--

## Printed-circuit board connector - MCV 0,5/ 7-G-2,5 BK - 1909582

### Approvals

cULus Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> E60425-19930913
		B
Nominal voltage UN		125 V
Nominal current IN		4 A

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>