



**NOTES:**

1 MATERIAL HOUSING: GREY GLASSFILLED POLYESTER  
UL 94 V-0  
CONTACT: PHOSPHOR BRONZE

2 GENERAL PLATING SPECIFICATION: UNDERPLATING (ENTIRE CONTACT): 1,27µm NICKEL MIN. AND ACTION PIN: 0,5µm TIN-LEAD MIN. FOR PLATING OF MATING SURFACES SEE APPLICABLE SPECIFICATION REFERENCE FOR EACH DASH NUMBER.

3 CONFORMS TO ALL TESTING ACCORDING IEC 61076-4-101 PERFORMANCE LEVEL 2.

4 CONFORMS TO ALL TESTING ACCORDING IEC 61076-4-101 PERFORMANCE LEVEL 1.

5 CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL III, CENTRAL OFFICE APPLICATIONS.

6 CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL III, UNCONTROLLED ENVIRONMENT APPLICATIONS.

7 CONNECTOR LUBRICATED WITH TELCORDIA GR-1217-CORE APPROVED LUBRICANT.

8 CONNECTOR MARKED WITH PARTNUMBER AND DATECODE

9 PLATED-THROUGH HOLES AT 2x2mm SQUARE GRID.

10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

11 0.76µm MIN GOLD PLATING AT MATING AREA.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: L.v.d.HEIJDEN 15DEC97	TE Connectivity	
DIMENSIONS: mm		CHK: D. TRUREN 15DEC97	Z-PACK 2MM HM TYPE B22 110 POS. RIGHT ANGLE MALE CONNECTOR ASSEMBLY	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD: F.v.KONINGSBRUGGE	SIZE: A2	CAGE CODE: 00779
0 PLC	± -	PRODUCT SPEC	DRAWING NO: C-352131	RESTRICTED TO: -
1 PLC	± -	APPLICATION SPEC	SCALE: NTS	SHEET: 1 of 1
2 PLC	± -	114-19029	REV: G2	
3 PLC	± -	WEIGHT: -		
4 PLC	± -	CUSTOMER DRAWING		
ANGLES	± -			
FINISH	-			