

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	03APR2015	DW	CW
	B	ECR-15-014907	14OCT2015	DL	CW

M4 THREAD  
RECOMMENDED  
TIGHTENING TORQUE 1.2Nm

4X M3 THREAD, RECOMMENDED  
TIGHTENING TORQUE 0.5Nm

PANEL CUT FOR INSERTS FOR USE  
WITHOUT HOODS/ HOUSINGS

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 500V  
RATED CURRENT: 16A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 6KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
OPERATION TEMPERATURE:  $-40+125^{\circ}C$   
WIRE RANGE: 0.14-4 mm<sup>2</sup> (26-12 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20300X10XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 500V  
额定电流: 16A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 6KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
工作温度:  $-40+125^{\circ}C$   
接线范围: 0.14-4 mm<sup>2</sup> (26-12 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20300X10XX000)

HEE-032-M 33-64	T2050642101-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	01APR2015	TE Connectivity NAME HEE-032-M 33-64
		CHK	01APR2015	
		APVD	01APR2015	
		PRODUCT SPEC	108-106137	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC
		0 PLC	±-	114-106137
		1 PLC	±-	WEIGHT
		2 PLC	±-	-
		3 PLC	±-	Customer Drawing
		4 PLC	±-	SCALE 1:1
		ANGLES	±-	SHEET 1 OF 1
MATERIAL		FINISH	-	RESTRICTED TO
				REV B

1470-19 (3/13)