



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

MIL-STD-348

Mateable with GPPO™ (Gilbert Engineering Co., Inc.)
and SSMP™ (Connectors Devices, Inc.)

Documents

N/A

Material and plating

Connector parts

Center contact
Outer contact
Dielectric
Substrate

Material

CuBe
CuBe
PTFE
Al₂O₃

Plating

Gold, min. 1.27 μ m, over nickel
Gold, min. 0.8 μ m, over nickel

Electrical data

Impedance	50 Ω
Frequency range	DC to 40 GHz
Return loss	≥ 26.4 dB, DC to 18 GHz ≥ 17.7 dB, 18 GHz to 26.5 GHz ≥ 16.6 dB, 26.5 GHz to 40 GHz
Power handling	≤ 0.5 W

Mechanical data

Mating cycles	
if mating part is Smooth bore	≥ 500
if mating part is Full detent	≥ 100
Center contact captivation	≥ 7 N
Engagement force	
- Smooth bore	11 N typical
- Full detent	19 N typical
Disengagement force	
- Smooth bore	11 N typical
- Full detent	29 N typical

Environmental data

Operating temperature range ¹	0 °C to +125 °C
Storage temperature range	- 55 °C to +155 °C
RoHS	compliant

¹ Temperature range over which these specifications are valid.

Packing

Standard	100 pcs in blister
Weight	0.3 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	16.02.05	Markus Müller	07.11.16	d00	15-1674	Marion Striegler	07.11.16
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2