


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 40.9              |
| B   | 27.6              |
| C   | 23.05             |
| D   | 4                 |
| E   | 54                |
| F   | 34.9              |
| G   | 44.5              |
| H   | M4                |



| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 8   | DOSENGEHÄUSE / SHELL                    |
| 20  | KURZES ENDGEHÄUSE/SHORT ENDBELL         |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change  
Drawings illustrate normal insulator positioning

Material Specification:

|                     |   |
|---------------------|---|
| Shell Material:     | Aluminium alloy                               |
| Shell Plating:      | Olive drab chromate over cadmium (conductive) |
| Insulator Material: | CR-Elastomere                                 |
| Contact Material:   | Copper alloy                                  |
| Contact Plating:    | Hard silver                                   |

all dimensions are in mm  
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
CUSTOMER



description CA3100R24A28S-B-F80  
Wall mounting receptacle  
Shortened light-weight endbell without cable clamp  
AWG Crimp / Socket / Layout: 24A28

© All rights reserved. Reproduction or issue to third in any form  
whenever is only permitted with written authorization of ITT Cannon



page 1/1  
revision 1488 30, Jul 18