



- NOTES
1. LEAD CO-PLANARITY SHALL BE 0.1mmMAX.
 - 2 DIRECTED CENTER LINE INDICATES THE CENTER OF 2.75±0.2 WHICH IS CONNECTOR DIMENSION. IT CORRESPONDS WITH THE CENTER LINE OF ENBOSSED POCKET.
 - 3 DIRECTED CENTER LINE INDICATES THE CENTER OF 2.57±0.02 WHICH IS RECOMMENDED LAND PATTERN DIMENSION. IT IS THE BASE LINE OF RECOMMENDED LAND PATTERN DIMENSION AND RECOMMENDED METAL MASK DIMENSION. IT CORRESPONDS WITH THE CENTER OF 2.37±0.2 WHICH IS CONNECTOR DIMENSION.
 - 4 CONDUCTIVE CIRCUIT ON THIS SURFACE REQUIRES THE COVERAGE WITH RESIST.
 - 5 IT INDICATES PROHIBITION AREA OF MOUNTING. IF PARTS WERE MOUNTED ON THIS AREA, THE LOCK OF CONNECTOR BECOMES DISABLED BECAUSE MOUNTED PARTS INTERFERE WITH THE LATCH OF PLUG.
 6. PER REEL : 500 COMPONENTS.
 7. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
 - 8 REFER TO JIS 0806. (PACKING OF COMPONENTS FOR AUTO HANDRING)

2	LCP	UL94V-0, BLACK	6	PS	BLACK
1	PHOSPHOR BRONZE	CONTACT AREA : Au PLATING 0.1μm MIN. LEAD AREA : Au PLATING 0.05μm MIN. UNDER PLATING : Ni PLATING 1μm MIN.	5	POLYESTER	CLEAR
			4	PS	CLEAR
			3	SUS	CONTACT AREA : Au PLATING 0.05μm MIN. LEAD AREA : Au PLATING 0.05μm MIN. UNDER PLATING : Ni PLATING 0.2μm MIN.
部番	材 質	処 理 , 備 考	部番	材 質	処 理 , 備 考
UNITS mm		SCALE 5 : 1		訂 正 記 事	設 計
HRS HIROSE ELECTRIC CO., LTD.		承認 : MH. YAMANE 13.11.26	検 査 : MH. TSUCHIDA 13.11.25	設 計 : AH. MIYAZAKI 13.11.12	製 図 : AH. MIYAZAKI 13.11.12
			図番 :	EDC3-339516-02	
			製品名 :	DF81-40S-0.4H(52)	
			製品コード :	CL662-8100-4-52	

MICRO COAXIAL CABLE AWG#36~AWG#46
DISCRETE CABLE AWG#34~AWG#40

