

**Technical Data Sheet****Electro-Wash<sup>®</sup> MX Cleaner Degreaser  
Presaturated Wipe****PRODUCT DESCRIPTION**

Electro-Wash<sup>®</sup> MX Cleaner Degreaser is a high flash point cleaner that quickly removes soils, adhesives, and residues from insulation jackets and conductors on telecom, fiber optic and coaxial cables. Engineered with very low surface tension, this formulation penetrates and removes soils quickly with excellent wetting action, lifting and removing soils from the dirtiest areas. Electro-Wash<sup>®</sup> MX Cleaner Degreaser is also ideal for removing carbonization, oxidized oils and greases from metal surfaces.

- Removes encrusted dirt, grease, silicone and other contaminants
- Removes flooding compound and “ickypic”
- Moderate evaporation
- Leaves no residues
- Low odor
- Contains no CFCs or HCFCs
- Contains no chlorinated solvents

**TYPICAL APPLICATIONS**

Electro-Wash<sup>®</sup> MX Cleaner Degreaser is engineered to clean:

- Fiber Optics & Connectors
- Cables
- Hard-line Coax Cable
- Metal & Fiber Optic Cable Splices
- PC Boards
- Motors & Transformers
- Control Systems
- Screens & Stencils

**TYPICAL PRODUCT DATA AND  
PHYSICAL PROPERTIES**

<b>Boiling Point</b>	239° F Initial
<b>Flash Point (TCC)</b>	45° F
<b>Evaporation Rate (butyl acetate=1)</b>	>1
<b>Specific Gravity</b>	0.72
<b>Appearance</b>	Clear, Colorless Liquid
<b>Odor</b>	Hydrocarbon
<b>Kauri-Butanol (KB) Number</b>	29
<b>Solubility in Water</b>	Negligible
<b>Shelflife</b>	5 years

**COMPATIBILITY**

Electro-Wash<sup>®</sup> MX Cleaner Degreaser is generally compatible with most materials. As with any cleaning agent, solvent/component compatibility must be determined on a non-critical area prior to use.

<u>Material</u>	<u>Compatibility</u>
ABS	Excellent
Buna-N	Excellent
EPDM	Excellent
Graphite	Excellent
HDPE	Excellent
Kynar™	Excellent
LDPE	Excellent
Lexan™	Excellent
Neoprene	Excellent
Noryl®	Excellent
Nylon 66™	Excellent
Cross-Linked PE	Excellent
Polypropylene	Excellent
Polystyrene	Excellent
PVC	Excellent
Silicone Rubber	Excellent
Teflon™	Excellent
Viton™	Excellent

**TECHNICAL & APPLICATION ASSISTANCE**

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

**ENVIRONMENTAL IMPACT DATA**

ENVIRONMENTAL IMPACT DATA			
CFC	0.0%	VOC	100%
HCFC-141b	0.0%	HFC	0.0%
HCFC-225	0.0%	nPB	0.0%

CFC, HCFC-225, HCFC-141b, VOC, HFC, and nPB percentages shown are the content by weight.

**NOTE:**

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS® does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

**CHEMTRONICS**  
**8125 COBB CENTER DRIVE**  
**KENNESAW, GA 30152**

1-770-424-4888 REV. B (08/13)

**USAGE INSTRUCTIONS**

For commercial use only.  
 Read MSDS carefully prior to use.  
 Remove wipe from packets and lightly wipe away any dust or contaminants from surfaces. Allow surface to dry completely before use.

**AVAILABILITY**

CP421 Presaturated Wipes (25/box)

Chemtronics® and Electro-Wash® are registered trademarks of Chemtronics. All rights reserved.

<u>DISTRIBUTED BY:</u>