



General ordering data

Order No.	1720750000
Part designation	ZDL 2.5S/NT/L/PE
Version	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
EAN	4008190380359
Qty.	50 pc(s).

Product notes

Note, ordering data	Spacing between mounting plates should be 200mm.
Note, technical data	2.5 mm ² flexible conductors with wire end ferrules are crimped with the Weidmüller PZ 6/5 crimping tool.
Product description	N-cross-connections with busbar system 10 x 3 mm.
Note, accessories	The supply to the busbar is via a busbar connection (ZB 35, ZB 16 or ZF 4S).

Additional technical data

Colour of insulating material	dark beige
Connection direction	Inclined / angled
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of levels	2
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Tension clamp connection
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0

Additional technical data

Version 3-conductor installation terminal

CSA rating data

Voltage (CSA) 300 V
 CSA current 10 A
 Min. cross-section (CSA) AWG 26
 Max. cross-section (CSA) AWG 12

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1) 0.5 mm²
 Flexible with ferrule, max. (DIN 46228 pt 1) 2.5 mm²

Conductors for clamping (rated connection)

Clamping range, min. 0.13 mm²
 Clamping range, max. 4 mm²
 Type of connection Tension clamp connection
 Connection direction Inclined / angled
 No. of connections 5
 Stripping length 8 mm
 Blade size 0.6 x 3.5 mm
 Gauge to IEC 60947-1 A2
 Solid, min. 0.5 mm²
 Solid, max. 4 mm²
 Flexible, min. 0.5 mm²
 Flexible, max. 4 mm²
 Flexible with ferrule, min. (DIN 46228/1) 0.5 mm²
 Flexible with ferrule, max. (DIN 46228/1) 2.5 mm²
 Flexible, min., ferrule with plastic collar (DIN 46228 pt 4) 0.5 mm²
 Flexible, max., ferrule with plastic collar (DIN 46228 pt 4) 2.5 mm²
 AWG conductor size, min. AWG 26
 AWG conductor size, max. AWG 12

Dimensions

Width 5.1 mm
 Height of lowest version 48.5 mm
 Length 95 mm
 TS 35 offset 49 mm

Distribution terminals

N-function Yes
 No. of potentials 2
 PE function Yes
 Rated impulse withstand voltage to N/PE 4 kV
 Rated voltage to N/PE 250 V

N-conductor disconnect terminal

For N-busbar 3 x 10 mm

Rating data

Rated cross-section	2.5 mm ²
Rated voltage	400 V
Rated impulse voltage	4 kV
Rated current	24 A
Standards	IEC 60947-7-1 (-7-2)
Current with max. conductor	24 A
Pollution severity	3

UL rating data

Voltage (UL)	300 V
Current (UL)	10 A
Min. cross-section (UL)	AWG 26
Max. cross-section (UL)	AWG 12

Approvals

Approvals institutes



Downloads

STEP	1720750000_26394_ZDL_2.5_S-NT-L-PE_STP.stp
------	--

Classifications

ETIM 2.0	EC001329
ETIM 3.0	EC001329
eClass 4.1	27-14-11-25
eClass 5.0	27-14-11-25
eClass 5.1	27-14-11-25

Similar products

Order No.	Part designation	Version
1720780000	ZDL 2.5 S/L	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720760000	ZDL 2.5 S/L/L	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720810000	ZDL 2.5 S/L/L/PE	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720770000	ZDL 2.5 S/N	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720790000	ZDL 2.5 S/N/L	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35

1720800000 ZDL 2.5 S/N/L/PE

Storey installation terminal, 2.5 mm², Tension clamp connection,
Wemid, dark beige, TS 35