

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	BI	REVISED (ECR-16-005149)	15. JAN. '16	SM	HG

CODING-A (P/N: 1897725-2)

TABLE 1. APPLICABLE TAB CONTACT.

TAB	PART NO.	WIRE RANGE (mm ²)	INSULATION DIA. (mm) (FLR)
MCP 1.5	969028	0.2-0.5	1.2-1.6
	964269	0.5-1.0	1.4-2.1
	△ 1703278	1.25-1.5	1.4-2.1

TABLE 2. APPLICABLE SINGLE WIRE SEALS.

WIRE RANGE (mm ²)	INSULATION DIA. (mm)	COLOR	PART NO.
0.35-0.50	1.2~1.6	RED	964971-1
0.50-0.75	1.4~1.9	GRAY	963530-1
1.0	1.9~2.1	YELLOW	964972-1
△ 1.25	1.9~2.4	ORANGE	2112323-1

CODING-B (P/N: 1-1897725-3)

TABLE 3. APPLICABLE DEAD END PLUG

APPLICABLE ASS'Y P/N	△ DEAD END PLUG	COLOR	PART NO.
1-1897726-2	DEAD END PLUG	WHITE	963531-1
		NATURAL	1394132-1
2-1897726-3	DEAD END PLUG	NATURAL	1394132-1

Missing dimension see
P/N: 1897726-2

NOTE ;

- GENERAL TOLERANCE : ± 0.3 , $\pm 3.0^\circ$
- APPLICABLE TAB CONTACT : SEE TABLE 1.
- APPLICABLE SINGLE WIRE SEAL : SEE TABLE 2.
- THE MATING REC. HSG ASS'Y P/N :
1897726-2 / 1-1897726-2 / 2-1897726-3
CIRCUIT NO.
TAB CONTACT (P/N: 1703278) AND SINGLE WIRE SEALS (P/N: 2112323-1)
SHOULD BE USED TO ONLY MATING REC. HSG ASS'Y (P/N: 1-1897726-2).
DEAD END PLUG INSERTION DEPTH: $1.5\text{mm}^{+1.5}_0$
- APPLICABLE COVER P/N : 2219418-2

B 7

DEAD END PLUG INSERTION DEPTH: $1.5\text{mm}^{+1.5}_0$

SCALE 5:1

 $1.5^{+1.5}_0$

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	\pm
1 PLC	± 0.5
2 PLC	± 0.13
3 PLC	± 0.013
4 PLC	± 0.0001
ANGLES	\pm

MATERIAL

FINISH

DWN

SM LEE

CHK

KT LIM

APVD

HG CHO

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

B 1

1-1897725-3	TAB HSG	PBT-GF15	GRAY
1897725-2	TAB HSG	PBT-GF15	BLACK
PART NO.	DESCRIPTION	MATERIAL	COLOR

TE Connectivity

NAME

MCPI.5 SEALED 10P TAB HSG

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779

C-1897725

CUSTOMER DRAWING

SCALE

1:1

SHEET

OF

1

REV

BI

1470-19 (3/13)