



Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.




KSC5338D/KSC5338DW

NPN Triple Diffused Planar Silicon Transistor

Features

- High Voltage Power Switch Switching Application
- Wide Safe Operating Area
- Built-in Free-Wheeling Diode
- Suitable for Electronic Ballast Application
- Small Variance in Storage Time
- Two Package Choices : TO-220 or D²-PAK



Absolute Maximum Ratings $T_a=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	1000	V
V_{CEO}	Collector-Emitter Voltage	450	V
V_{EBO}	Emitter-Base Voltage	12	V
I_C	Collector Current (DC)	5	A
I_{CP}	*Collector Current (Pulse)	10	A
I_B	Base Current (DC)	2	A
I_{BP}	*Base Current (Pulse)	4	A
P_C	Power Dissipation ($T_C=25^\circ\text{C}$)	75	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature	- 55 to 150	$^\circ\text{C}$

* Pulse Test : Pulse Width = 5ms, Duty Cycle \leq 10%

Thermal Characteristics

Symbol	Parameter	Rating	Units	
$R_{\theta jc}$	Thermal Resistance	Junction to Case	1.65	$^\circ\text{C}/\text{W}$
$R_{\theta ja}$		Junction to Ambient	62.5	$^\circ\text{C}/\text{W}$
T_L	Maximum Lead Temperature for Soldering		270	$^\circ\text{C}$

Electrical Characteristics $T_a=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units	
BV_{CBO}	Collector-Base Breakdown Voltage	$I_C=1\text{mA}, I_E=0$	1000			V	
BV_{CEO}	Collector-Emitter Breakdown Voltage	$I_C=5\text{mA}, I_B=0$	450			V	
BV_{EBO}	Emitter-Base Breakdown Voltage	$I_E=1\text{mA}, I_C=0$	12			V	
I_{CBO}	Collector Cut-off Current	$V_{CB}=800\text{V}, I_E=0$			10	μA	
I_{CES}	Collector Cut-off Current	$V_{CES}=1000\text{V}, I_{EB}=0$	$T_a=25^\circ\text{C}$		100	μA	
			$T_a=125^\circ\text{C}$		500	μA	
I_{CEO}	Collector Cut-off Current	$V_{CE}=450\text{V}, I_B=0$	$T_a=25^\circ\text{C}$		100	μA	
			$T_a=125^\circ\text{C}$		500	μA	
I_{EBO}	Emitter Cut-off Current	$V_{EB}=10\text{V}, I_C=0$			10	μA	
h_{FE}	DC Current Gain	$V_{CE}=1\text{V}, I_C=0.8\text{A}$	$T_a=25^\circ\text{C}$	15	25		
			$T_a=125^\circ\text{C}$	10	14		
		$V_{CE}=1\text{V}, I_C=2\text{A}$	$T_a=25^\circ\text{C}$	6	9		
			$T_a=125^\circ\text{C}$	4	6		
		$V_{CE}=2.5\text{V}, I_C=1\text{A}$	$T_a=25^\circ\text{C}$	18	25		
			$T_a=125^\circ\text{C}$	14	18		
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=0.8\text{A}, I_B=0.08\text{A}$	$T_a=25^\circ\text{C}$		0.35	0.5	V
			$T_a=125^\circ\text{C}$		0.55	0.75	V
		$I_C=2\text{A}, I_B=0.4\text{A}$	$T_a=25^\circ\text{C}$		0.47	0.75	V
			$T_a=125^\circ\text{C}$		0.9	1.1	V
		$I_C=0.8\text{A}, I_B=0.04\text{A}$	$T_a=25^\circ\text{C}$		0.9	1.5	V
			$T_a=125^\circ\text{C}$		1.8	2.5	V
		$I_C=1\text{A}, I_B=0.2\text{A}$	$T_a=25^\circ\text{C}$		0.22	0.5	V
			$T_a=125^\circ\text{C}$		0.3	0.6	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=0.8\text{A}, I_B=0.08\text{A}$	$T_a=25^\circ\text{C}$		0.8	1.0	V
			$T_a=125^\circ\text{C}$		0.65	0.9	V
		$I_C=2\text{A}, I_B=0.4\text{A}$	$T_a=25^\circ\text{C}$		0.9	1.0	V
			$T_a=125^\circ\text{C}$		0.8	0.9	V
C_{ib}	Input Capacitance	$V_{EB}=10\text{V}, I_C=0.5\text{A}, f=1\text{MHz}$		550	750	pF	
C_{ob}	Output Capacitance	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$		60	100	pF	
f_T	Current Gain Bandwidth Product	$I_C=0.5\text{A}, V_{CE}=10\text{V}$		11		MHz	
V_F	Diode Forward Voltage	$I_F=1\text{A}, I_C=1\text{mA}, I_E=0$	$T_a=25^\circ\text{C}$		0.86	1.3	V
			$T_a=125^\circ\text{C}$		0.79		V
		$I_F=2\text{A}$	$T_a=25^\circ\text{C}$		0.95	1.5	V
			$T_a=125^\circ\text{C}$		0.88		V
t_{fr}	Diode Forward Recovery Time ($di/dt=10\text{A}/\mu\text{s}$)	$I_F=0.4\text{A}$		460		ns	
		$I_F=1\text{A}$		360		ns	
		$I_F=2\text{A}$		325		ns	
$V_{CE(DSAT)}$	Dynamic Saturation Voltage	$I_C=1\text{A}, I_{B1}=100\text{mA}$ $V_{CC}=300\text{V}$ at $1\mu\text{s}$	$T_a=25^\circ\text{C}$		8		V
			$T_a=125^\circ\text{C}$		15		V
		$I_C=1\text{A}, I_{B1}=100\text{mA}$ $V_{CC}=300\text{V}$ at $3\mu\text{s}$	$T_a=25^\circ\text{C}$		2.9		V
			$T_a=125^\circ\text{C}$		8		V
		$I_C=2\text{A}, I_{B1}=400\text{mA}$ $V_{CC}=300\text{V}$ at $1\mu\text{s}$	$T_a=25^\circ\text{C}$		9		V
			$T_a=125^\circ\text{C}$		17		V
		$I_C=2\text{A}, I_{B1}=400\text{mA}$ $V_{CC}=300\text{V}$ at $3\mu\text{s}$	$T_a=25^\circ\text{C}$		1.9		V
			$T_a=125^\circ\text{C}$		8.5		V

Electrical Characteristics (Continued) $T_a=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Min	Typ.	Max.	Units	
RESISTIVE LOAD SWITCHING (D.C. $\leq 10\%$, Pulse Width=40 μs)							
t_{ON}	Turn On Time	$I_C=2.5\text{A}$, $I_{B1}=500\text{mA}$, $I_{B2}=-1\text{A}$, $V_{\text{CC}}=250\text{V}$, $R_L = 100\Omega$		500	750	ns	
t_{STG}	Storage Time		1.2		1.5	μs	
t_{F}	Fall Time			100	200	ns	
t_{ON}	Turn On Time	$I_C=2\text{A}$, $I_{B1}=400\text{mA}$, $I_{B2}=-1\text{A}$, $V_{\text{CC}}=300\text{V}$, $R_L = 150\Omega$	$T_a=25^\circ\text{C}$	100	150	ns	
			$T_a=125^\circ\text{C}$		150	ns	
t_{STG}	Storage Time		$T_a=25^\circ\text{C}$	1.4	2.2	μs	
			$T_a=125^\circ\text{C}$		1.7	μs	
t_{F}	Fall Time		$T_a=25^\circ\text{C}$		90	150	ns
			$T_a=125^\circ\text{C}$		150	ns	
t_{ON}	Turn On Time	$I_C=2.5\text{A}$, $I_{B1}=500\text{mA}$, $I_{B2}=-5\text{mA}$, $V_{\text{CC}}=300\text{V}$, $R_L = 120\Omega$	$T_a=25^\circ\text{C}$		120	150	ns
			$T_a=125^\circ\text{C}$		150	ns	
t_{STG}	Storage Time		$T_a=25^\circ\text{C}$	1.8		2.1	μs
			$T_a=125^\circ\text{C}$		2.6	μs	
t_{F}	Fall Time		$T_a=25^\circ\text{C}$		110	150	ns
			$T_a=125^\circ\text{C}$		160	ns	
INDUCTIVE LOAD SWITCHING ($V_{\text{CC}}=15\text{V}$)							
t_{STG}	Storage Time	$I_C=2.5\text{A}$, $I_{B1}=500\text{mA}$, $I_{B2}=-0.5\text{A}$, $V_Z=350\text{V}$, $L_C=300\mu\text{H}$	$T_a=25^\circ\text{C}$		1.9	2.2	μs
			$T_a=125^\circ\text{C}$		2.4	μs	
t_{F}	Fall Time		$T_a=25^\circ\text{C}$		160	200	ns
			$T_a=125^\circ\text{C}$		330	ns	
t_{C}	Cross-over Time		$T_a=25^\circ\text{C}$		350	500	ns
			$T_a=125^\circ\text{C}$		750	ns	
t_{STG}	Storage Time	$I_C=2\text{A}$, $I_{B1}=400\text{mA}$, $I_{B2}=-0.4\text{A}$, $V_Z=300\text{V}$, $L_C=200\mu\text{H}$	$T_a=25^\circ\text{C}$	1.95		2.25	μs
			$T_a=125^\circ\text{C}$		2.9	μs	
t_{F}	Fall Time		$T_a=25^\circ\text{C}$		120	150	ns
			$T_a=125^\circ\text{C}$		270	ns	
t_{C}	Cross-over Time		$T_a=25^\circ\text{C}$		300	450	ns
			$T_a=125^\circ\text{C}$		700	ns	
t_{STG}	Storage Time	$I_C=1\text{A}$, $I_{B1}=100\text{mA}$, $I_{B2}=-0.5\text{A}$, $V_Z=300\text{V}$, $L_C=200\mu\text{H}$	$T_a=25^\circ\text{C}$		0.6	0.8	μs
			$T_a=125^\circ\text{C}$		1.0	μs	
t_{F}	Fall Time		$T_a=25^\circ\text{C}$		70	ns	
			$T_a=125^\circ\text{C}$		110	ns	
t_{C}	Cross-over Time		$T_a=25^\circ\text{C}$		80	130	ns
			$T_a=125^\circ\text{C}$		170	ns	

Typical Characteristics




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. DC current Gain




Figure 4. Collector-Emitter Saturation Voltage




Figure 5. Collector-Emitter Saturation Voltage




Figure 6. Base-Emitter Saturation Voltage

Typical Characteristics (Continued)




Figure 7. Base-Emitter Saturation Voltage




Figure 8. Collector Output Capacitance




Figure 9. Forward Recovery Time




Figure 10. Switching Time




Figure 11. Induction Storage Time




Figure 12. Inductive Crossover Time

Typical Characteristics (Continued)




Figure 13. Inductive Fall Time




Figure 14. Safe Operating Area




Figure 15. Reverse Bias Safe Operating




Figure 16. Power Derating





Figure 17. RBSOA Saturation

Physical Dimensions

TO-220








Dimensions in Millimeters



TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™	F-PFS™	Power-SPM™	 <p>SYSTEM GENERAL® The Power Franchise® the power franchise TinyBoost™ TinyBuck™ TinyCalc™ TinyLogic® TINYOPTO™ TinyPower™ TinyPWM™ TinyWire™ TriFault Detect™ TRUECURRENT™* µSerDes™  SerDes® UHC® Ultra FRFET™ UniFET™ VCX™ VisualMax™ XS™</p>
Auto-SPM™	FRFET®	PowerTrench®	
Build it Now™	Global Power Resource SM	PowerXS™	
CorePLUS™	Green FPS™	Programmable Active Droop™	
CorePOWER™	Green FPS™ e-Series™	QFET®	
CROSSVOLT™	Gmax™	QS™	
CTL™	GTO™	Quiet Series™	
Current Transfer Logic™	IntelliMAX™	RapidConfigure™	
DEUXPEED®	ISOPLANAR™	 ™	
Dual Cool™	MegaBuck™	Saving our world, 1mW/W/kW at a time™	
EcoSPARK®	MICROCOUPLER™	SignalWise™	
EfficientMax™	MicroFET™	SmartMax™	
ESBC™	MicroPak™	SMART START™	
 ®	MicroPak2™	SPM®	
Fairchild®	MillerDrive™	STEALTH™	
Fairchild Semiconductor®	MotionMax™	SuperFET™	
FACT Quiet Series™	Motion-SPM™	SuperSOT™-3	
FACT®	OptoHiT™	SuperSOT™-6	
FAST®	OPTOLOGIC®	SuperSOT™-8	
FastvCore™	OPTOPLANAR®	SupreMOS®	
FETBench™	 ®	SyncFET™	
FlashWriter®*	PDP SPM™	Sync-Lock™	
FPS™			

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local
Sales Representative