


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 40.9              |
| B   | 25.4              |
| C   | 1 7/16-18UNEF-2A  |
| D   | 9.5               |
| E   | 23.05             |
| F   | 4                 |
| G   | 62                |
| H   | 34.9              |
| I   | 44.5              |
| K   | M4                |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |
| 14  | F-ENDGEHÄUSE / F-ENDBELL            |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

**Material Specification:**  
 Shell Material: Aluminium alloy  
 Shell Plating: Olive drab chromate over cadmium (conductive)  
 Insulator Material: CR-Elastomere  
 Contact Material: Copper alloy  
 Contact Plating: Hard silver

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
 CUSTOMER



Engineered for life  
 ITT CANNON GmbH  
 D - 71384 Weinstadt/Germany

description CA3100F24-20PXB-F80  
 Wall mounting receptacle  
 Endbell for flex tube  
 AWG Crimp / Pin / Layout: 24-20

© All rights reserved. Reproduction or issue to third in any form  
 whatever is only permitted with written authorization of ITT Cannon



page 1/1  
 revision 1488 30. Jul 18