

1

2

3

4

A

B

C

D

A

B

C

D

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:

SEE GS-12-447

NOTE-2: COMPATIBLE WITH NARROW AND WIDE BODY

NOTE-3: PCB FINISH HOLE DIAMETER : SEE GS-12-447

NOTE-4: STANDARD PACKAGING IS IN TUBE ,BUT IF SUFFIX "P"  
IS ADDED IN P/N ,PACKAGING IS IN TRAYS ,BUT CONNECTOR  
MARKING IS WITHOUT "P"  
Example: HM1FxxxxxxxH6PLF, marking: HM1FxxxxxxxH6LF

SPECIFIC DATAS:

Visual inspection : 100%

- Marking failures
- Housing material failures
- Spoilt housing
- Stained housing
- Broken contacts ( twisted or loosen )

LAYOUT FOR P.C.B

scale : 2.5

△ PART NUMBER

HM1S41FER400H\*(LF)

LF = FOR LEAD FREE PRODUCT

PLATING CODE:

6 = TELCORDIA CO

E = CUSTOMER SPECIAL, CONTACT

30u" GOLD SELECTIVE PLATING.

European Views

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection 	mm 
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	PERRICHOT	2001/01/26	ANGULAR	0.X	±0.1
Eng	LENOIR	2001/01/26	LINEAR	0.XX	±0.1
Chr	LEGARE	2001/01/26	0.XX ±2	0.XXX	±0.1
Appr	LEGARE	2001/01/26	Product family	METRAL	Spec ref -
rev	ecn no	dr	date		
A	-	-	2001/01/26		
B	LS05-004	MLE	2005/02/22		
C	LS06-0095	LGO	2006/07/05		
D	LS06-0159	MLE	2006/10/24		
E	LS07-0266	MLE	2007/11/09		
F	DG09-0367	TER	2009-11-25		
-	-	-	-		
title METRAL FEM. 4 ROW STRAIGHT PRESS FIT PCB THICKNESS 2.4 mm MINIMUM			dwg no C-8626-1110	Rev. F	
catalog no			CUSTOMER	sheet	1 of 1

REV F - 2006-04-17

1

2

3

4

PDM: Rev:F

STATUS:Released

Printed: Jan 13, 2010

FCI

Copyright FCI.