

**SCHEMATIC**

**SPECIFICATIONS**

**FUNCTION:** 2P1T OFF-ON  
**RATINGS:**  
ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E194579):  
20A 125VAC [UR-clB]  
18A 125VAC 1/4HP [cURus]  
18A 250VAC 1/4HP [cURus]  
6.9A 250VAC 3/4HP [cURus]  
ANSI/UL 1054 (233821):  
18A 125VAC 1/4HP [CSAus]  
18A 250VAC 1/4HP [CSAus]  
EN 61058-1:2002 and DIN/VDE 0830-1:2003-03 (40017928):  
18(A) 250V~ T12S/5S 1E4 [ENEC10, VDE]  
10(A) 250V~ T12S/5S 1E4 [ENEC10, VDE]  
18(A) 250V~ T12S/5S 1E4 [ENEC10, VDE]

**ILLUMINATION VOLTAGE:** 125V

**CONTACT RESISTANCE:** Inhd: 20mΩ Max.

**INSULATION RESISTANCE:** 100MΩ Min. at 500VDC

**DIELECTRIC STRENGTH:** 1,000VAC For 1 Minute

**ELECTRICAL LIFE:** 6,000 Cycles [cURus, CSAus]  
10,000 Cycles [ENEC10, VDE]  
50,000 Cycles [ENEC10, VDE: 10(2)A 250V~]

**TEMPERATURE:** -20°C to 65°C [cURus]  
-20°C to 125°C [ENEC10, VDE]


**APPROVALS:**

**COLORS AND MARKINGS**

**BODY:** Black  
**ACTUATOR:** Transparent Red  
**MARKING:** None  
**MARKING COLOR:** None  
**FRAME:** Black

**MATERIALS**

**BODY:** Polyamide 6/6 (PA66), UL94 V-2  
**ACTUATOR:** Polycarbonate (PC), UL94 V-2  
**LAMP CARRIER:** Polyamide 6/6 (PA66), UL94 V-2  
**LAMP:** Neon Bulb  
**SPRING:** Piano Wire  
**CONTACTS:** Silver Alloy  
**TERMINALS:** Silver Plated Copper  
Silver Plated Brass  
**CAP:** Polyvinyl Chloride (PVC)  
**FRAME:** Polyamide 6/6 (PA66), UL94 V-2



PANEL THICKNESS		X
0.030~0.049 [0.75~1.25]	1.189 [30.2]	
0.048~0.078 [1.25~2.00]	1.200 [30.5]	

ACTUATOR	A	09/07/02	CAB
BODY	A	09/07/08 <td>CAB</td>	CAB
COLORS	A	09/07/08 <td>CAB</td>	CAB
MATERIALS	A	09/07/08 <td>CAB</td>	CAB
SPECIFICATIONS	A	09/07/02 <td>CAB</td>	CAB
REFERENCE	REV.	DATE	BY

1 2 3

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

UPDATE DESCRIPTION	30355	12/21/11	BMA
INITIAL RELEASE	11893 <td>10/02/22 <td>CAB</td> </td>	10/02/22 <td>CAB</td>	CAB
DESCRIPTION	FOR <td>DATE <td>DRAWN BY </td></td>	DATE <td>DRAWN BY </td>	DRAWN BY

DIMENSIONS	
INCHES [MILLIMETERS]	
GENERAL TOLERANCES	±0.008 [±0.2] / ±1'
SCALE	DRAWING NOT TO SCALE
PROJECTION	

**E-SWITCH**

**LAMB INDUSTRIES**

RB242D1000-116ACCFO21

DATE: FEBRUARY 22, 2010

REVISION: B