

- ▶ [Cable Ties](#)
- ▶ [Cable Ties with Fasteners](#)
- ▶ [Cable Tie Tools](#)
- ▶ [Clamps and Clips](#)
- ▶ [Heatshrink Moulded Shapes](#)
- ▶ [Mounts](#)
- ▶ [Heavy Duty Mounts](#)
- ▶ [Wire Connectors](#)
- ▶ [Wiring Duct](#)
- ▶ [Wiring Protection](#)
- ▶ [Labels, Printers and Software](#)
- ▶ [Pre-Terminated Networking](#)
- ▶ [Copper Network Solutions](#)
- ▶ [Fiber Network Solutions](#)
- ▶ [Jacks and Wall Plates](#)
- ▶ [Racks - Cable Management](#)
- ▶ [Surface Raceway Systems](#)

## T30LOUVC2

Standard Cable Tie, 7.8" Long, 30lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number: 111-00437

Part Number: T30LOUVC2

Type: T30L

→ [Find a Distributor](#)

→ [Order Samples](#)

→ [Get Technical Drawings](#)

### Base Data

<b>Part No.</b>	T30LOUVC2
<b>Type</b>	T30L
<b>Color</b>	Black (BK)
<b>Features</b>	<ul style="list-style-type: none"> <li>• UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .</li> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
<b>Application Method</b>	Quick, simple fixing by hand or with HellermannTyton tensioning tools
<b>Identification Plate Position</b>	none
<b>Releasable Closure (Yes/No)</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Typical Application</b>	Used to bundle and secure wire and cable.
<b>Variant</b>	Inside Serrated

### Product Dimensions

<b>Min. Tensile Strength</b>	30.0lbs / 135.0N
<b>Length (L)</b>	198.0mm
<b>Width (W)</b>	3.6mm
<b>Min. Ø Bundle</b>	1.5mm
<b>Max. Ø Bundle</b>	50.0mm

### Material and Specifications

<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV)
<b>Flammability</b>	UL94 V2
<b>Material Specification</b>	HF / RoHS
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	RoHS
<b>Specification</b>	UL ZODZ2.E64139
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No

 **Logistic and Packaging**

<b>Packaging Type</b>	bag
<b>Pkg. Qty.</b>	100
<b>UPC</b>	089306272588

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)

[Home](#) | [About HellermannTyton](#) | [Products](#) | [Careers](#) | [Contact](#) | [Terms](#)

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001](#) Certified  
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512