

Specification Sheet

Part Number: T120L0K2



Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Black, 50/pkg

Article Number	111-12405
Type	T120L
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Heavy-duty design offers higher tensile strength.• Buckle feature on head allows excess strap to be tucked away after installation.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description

Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Black, 50/pkg

Global Part Name

T120L-PA66-BK

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535.0

Length L (Imperial)

30.0

Length L (Metric)

760.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.30

Width W (Metric)

7.6

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

8.85

Bundle Diameter Max (Metric)

224.8

Thickness T (Metric)

1.9

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

US MIL SPEC

MIL 53421

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

UL-ZODZ2.E64139

UL Recognized (US)

Yes

UL Listed (US and Canada)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

50

Package Quantity (Metric)

50

Customs Number

3926909987

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)