



P1	P2
1 WHITE	6
2 BLACK	5
3 RED	4
4 GREEN	3
5 YELLOW	2
6 BLUE	1

Note:
 • Material: Housing-polycarbonate, clear
 Terminal-0.36[.014] thick phosphor bronze.
 Thick gold in localized gold plate.
 Area, Gold Flash over the remainder.
 Over 2.54mm[.000100] thick nickel underplate.

2.4±0.2
 SEC:△=△



A, B, C, D



E, F, G

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/6/S-5	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-6/6/S-7	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-6/6/S-10	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-6/6/S-12	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-6/6/S-14	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-6/6/S-25	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-6/6/S-50	G	15,250±150(50ft)	Silver	15,250-15,260mm

Unit: mm



Scale	Free				Date	Name	
TOLERANCE					Drawn	08.07.13	Wilson
X.	±X				Approved	08.07.13	Groll
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name		

Title	
Modular cable - Straight	
6P6C 50µ", 26AWG, Silver, 5-50 feet	
ASSMANN WSW-No.	
AT-S-26-6/6/S-xx	
Drawing-No.	
Replace	rev00
Sheet	1/1

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
 Toll Free: 1-877-277-6266 • Email: info@assmann.us