

# FL SWITCH MM HS/M

Order No.: 2832522




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2832522>

Modular switch system, head station, can be expanded to 24 ports, with GL rating



## Commercial data

|                          |  |
|--------------------------|--|
| GTIN (EAN)               | <br>4 046356 044059 |
| sales group              | K000   |
| Pack                     | 1 pcs.   |
| Customs tariff           | 85176200   |
| Catalog page information | Page 187 (AX-2009)   |

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Interfaces

|                      |  |
|----------------------|--|
| Interface            | Ethernet                                     |
| No. of ports         | 8 (Can be extended to a maximum of 24 ports) |
| Type of connection   | 8 ports via FL IF (interface) modules        |
| Transmission physics | Copper                                       |
| Transmission speed   | 10/100 MBit/s                                |
| No. of ports         | 8 (Can be extended to a maximum of 24 ports) |
| Type of connection   | 100BASE-FX                                   |
| Transmission physics | Multimode glass fiber                        |

|                     |  |
|---------------------|--|
| Transmission speed  | 100 MBit/s (full duplex)                                 |
| Transmission length | Up to 10000 m (depending on the fiber used)              |
|                     | 1300 nm  |
| Interface           | Serial (V.24 (RS-232))                                   |
| Type of connection  | V.24 (RS-232-C), 6-pos. MINI-DIN female connector (PS/2) |

**Function**

|                                  |  |
|----------------------------------|--|
| Basic functions                  | Store and forward switch complies with IEEE 802.3 2 priority classes in acc. with IEEE 802.1 P TCP/IP protocol, BootP-capable, port-mirroring, integrated web server function, multicast filtering, IGMP snooping, VLAN, Rapid Spanning Tree (RSTP), port security, PROFINET-IO-device, DHCP option 82 relay agent |
| Management                       | Integrated Management Agent, SNMP protocol (private MIB, MIB-2, RMON MIB, Bridge MIB), integrated Web server function  |
| Supported browsers               | Internet Explorer 5.5 or higher  |
| Redundancy                       | Spanning Tree 802.1d, Rapid Spanning Tree 802.1w, Fast Ring Detection, Media Redundancy Protocol (MRP) as per IEC 62439  |
| Status and diagnostic indicators | Per Ethernet 2 status LEDs: LINK and switch-over Status Activity, 100, full duplex, supply voltage $U_{S1}$ und $U_{S2}$ (redundant supply voltage) and FAIL, two-digit 7-segment display  |

**Network expansion parameters**

|  |  |
|--|--|
| Cascading depth                          | Network, linear, and star structure: any |
| Maximum conductor length ((twisted pair) | 100 m                                    |

**Supply voltage**

|                             |  |
|-----------------------------|--|
| Supply voltage              | 24 V DC  |
| Residual ripple             | 3.6 V <sub>PP</sub> (within the permitted voltage range) |
| Supply voltage range        | 18.5 V DC ... 30.5 V DC                                  |
| Typical current consumption | 350 mA (Up to 3500 mA, depending on the configuration)   |

**General data**

|   |                                  |
|---|----------------------------------|
| Weight                                  | 1350 g                           |
| Width                                   | 214 mm                           |
| Height                                  | 95 mm                            |
| Depth                                   | 107 mm                           |
| Degree of protection                    | IP20                             |
| Ambient temperature (operation)         | 0 °C ... 55 °C (no condensation) |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C                 |
| Permissible humidity (operation)        | 10 % ... 95 % (no condensation)  |

|  |  |
|--|--|
| Permissible humidity (storage/transport) | 10 % ... 95 % (no condensation)                  |
| Air pressure (operation)                 | 80 kPa ... 108 kPa (2000 above sea level)        |
| Air pressure (storage/transport)         | 70 kPa ... 108 kPa (3000 above sea level)        |
| Housing material                         | Zinc die-cast, surface bronzed and nickel-plated |
| Noise emission                           | EN 61000-6-3/-4                                  |
| Noise immunity                           | EN 61000-6-2:2005                                |

#### Mechanical tests

|              |  |
|--------------|--|
| Type of test | Shock test in acc. with IEC 60068-2-27                                 |
| Test result  | Operation: 25 g, 11 ms duration, semi-sinusoidal shock impulse         |
| Type of test | Shock test in acc. with IEC 60068-2-27                                 |
| Test result  | Storage/Transport: 50 g, 11 ms duration, semi-sinusoidal shock impulse |
| Type of test | Vibration resistance in acc. with IEC 60068-2-6                        |
| Test result  | Operation/Storage/Transport: 5 g, 150 Hz, Criterion 3                  |
| Type of test | Free fall in acc. with IEC 60068-2-32                                  |
| Test result  | 1 m  |

#### Conformity with EMC directives

|               |  |
|---------------|--|
| Test standard | IEC 61000-4-2 (ESD)                                |
| Test result   | Criterion B  |
| Test standard | IEC 61000-4-3 (immunity to radiated interference)  |
| Test result   | Criterion A  |
| Test standard | IEC 61000-4-4 (burst)                              |
| Test result   | Criterion A  |
| Test standard | IEC 61000-4-5 (surge)                              |
| Test result   | Criterion B  |
| Test standard | IEC 61000-4-6 (immunity to conducted interference) |
| Test result   | Criterion A  |
| Test standard | EN 55022 (emitted interference)                    |
| Test result   | Class A  |

#### Certificates / Approvals



Certification


ABS, BV, DNV, GL, GOST, LR

**Accessories**

| Item           | Designation       | Description  |
|----------------|-------------------|--|
| <b>General</b> |                   |  |
| 2832425        | FL IF 2FX SC-D    | FO media module for connecting 100Base-FX multimode glass fibers (1300 nm), connection direction downwards                                   |
| 2832205        | FL IF 2FX SM SC-D | FO interface module for connecting single mode (monomode) glass fibers (1300 nm) to the Factoryline Modular Managed Switch, output downwards |
| 2832357        | FL IF 2TX VS-RJ-D | Media module with two twisted pair ports for the modular managed switch system   |
| 2832344        | FL IF 2TX VS-RJ-F | Media module with two twisted-pair ports for the modular managed switch system, output towards the front                                     |
| 2832483        | FL IF MEM 2TX-D   | Memory module, 2 port twisted pair module for saving the switch configuration  |
| 2832535        | FL MXT/M          | Expansion, 8 Ethernet ports, with GL rating  |

**Diagrams/Drawings**

Dimensioned drawing



The illustration shows the head station FL SWITCH MM HS with interface module

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;