

## Specification Sheet

Part Number: T50I4M4



Standard Cable Tie, 12" Long, UL Rated, 50lb Tensile Strength, PA66, Yellow, 1000/pkg

Article Number	111-05244
Type	T50I
Color	Yellow (YE)
Features & Benefits	<ul style="list-style-type: none"><li>• Inside serrations allow for strong hold on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Standard Cable Tie, 12" Long, UL Rated, 50lb Tensile Strength, PA66, Yellow, 1000/pkg
<b>Global Part Name</b>	T50I-PA66-YE
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	12.0
<b>Length L (Metric)</b>	305.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	3.2
<b>Bundle Diameter Max (Metric)</b>	81.3

<b>Thickness T (Metric)</b>	1.2
-----------------------------	-----

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

<b>Material Shortcut</b>	PA66
--------------------------	------

<b>US MIL SPEC</b>	MS3367-7-4
--------------------	------------

<b>SAE-AS33671</b>	
--------------------	--

**Flammability**

UL 94 V2	<b>Halogen free</b>
----------	---------------------

Yes	<b>Operating Temperature (Metric)</b>
-----	---------------------------------------

-40°F to +185°F (-40°C to +85°C)	<b>ROHS Complaint</b>
----------------------------------	-----------------------

Yes	<b>Certification/Specification WEB</b>
-----	--

UL-ZODZ.E64139 CAGE Code 53421	<b>UL Recognized (US)</b>
--------------------------------	---------------------------

Yes	<b>UL Listed (US and Canada)</b>
-----	----------------------------------

Yes	<b>UL Recognized (US and Canada)</b>
-----	--------------------------------------

Yes	
-----	--

<b>Package Quantity(Imperial)</b>	1000
-----------------------------------	------

<b>Package Quantity (Metric)</b>	1000
----------------------------------	------

**Customs Number**

3926909987

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)