



Datasheet for part number CIR030FFP-14S-6P-F80-V0

| |
|---|
| Our Catalog Part Number: CIR030FFP-14S-6P-F80-V0 |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

| | |
|--|--|
| Product Datasheet | |
| SERIES | Connector with Bayonet Coupling |
| Shell Style | Rear Mount Receptacle - Square flange, with rear thread |
| Mounting | Flange with through mounting hole |
| Environmental Class | Backshell with A style clamp and bushing but includes wire sealing grommet and compression ring. |
| Shell Size | 14S |
| Contact Arrangement | 14S-6 |
| Total Number of contacts | 6 contacts |
| Number of Contacts Size 16S | 6 contacts size 16 |
| Gender | Pin |
| Contact Type | Crimp for AWG wire (used in F80 insert) |
| Contact Plating | Silver |
| Shell Material | Aluminium alloy |
| Shell Plating | Olive drab chromate over cadmium plating (conductive) |
| Contacts included | no, delivery without contacts |
| Shock Resistance | Waterproof to 10 meters (33 ft) 12 h (14.7 PSI) |
| Coupling | 2000 couplings minimum |
| Service Rating Letter | I |
| Operating Voltage DC | 250 V |
| Operating Voltage AC | 200 V |
| Dielectric strength - Minimum Flashover AC RMS | 1400 V |
| Dielectric strength - Test Voltage AC RMS (Hi Pot) | 1000 V |
| Note | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements. |