

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10°C TO 60 °C			
	VOLTAGE	250 V AC			APPLICABLE CONNECTORS	DF1E (A) - *EP-2, 5C			
	CURRENT	AWG22~20 : 3A			OPERATING HUMIDITY RANGE	UL1007,1061:AWG22~20			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			X	X
MARKING		CONFIRMED VISUALLY.						X	X
ELECTRIC CHARACTERISTICS									
CONTACT RESISTANCE		mA (DC OR 1000 Hz).			mΩ MAX.			--	--
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.		20 mV MAX 1 mA(DC OR 1000 Hz).			30 mΩ MAX.			X	--
INSULATION RESISTANCE		500 V DC.			MΩ MIN			--	--
VOLTAGE PROOF		650 V AC FOR 1 min.			NO FLASH OVER OR BREAKDOWN.			--	--
MECHANICAL CHARACTERISTICS									
CONTACT INSERTION AND EXTRACTION FORCES		BY STEEL GAUGE.			INSERTION FORCE EXTRACTION FORCE		N MAX. N MIN.	--	--
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE EXTRACTION FORCE		N MAX. N MIN.	--	--
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	--
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75mm, - m/s ² AT 2 h, FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1μs. ② CONTACT RESISTANCE: 30 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	--
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.			③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	--
ENVIRONMENTAL CHARACTERISTICS									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 →5 TO 35-85 →5 TO 35 °C TIME 30→ 5 MAX → 30 → 5 MAX min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE:1000MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	--
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: - MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	--
CORROSION SALT MIST		EXPOSED IN % SALT WATER SPRAY FOR h.			① CONTACT RESISTANCE: mΩ MAX. ② NO HAEAVY CORROSION.			--	--
HYDROGEN SULPHIDE		EXPOSED IN -- PPM FOR -- h. (TEST STANDARD: JEIDA-38)			① CONTACT RESISTANCE: mΩ MAX. ② NO HAEAVY CORROSION.			--	--
SULPHUR DIOXIDE		EXPOSED IN -- PPM FOR -- h. (TEST STANDARD: JEIDA-39)			① CONTACT RESISTANCE: mΩ MAX. ② NO HAEAVY CORROSION.			--	--
SOLDERING HEAT		SOLDER TEMPERATURE, °C FOR IMMERSION.DURATION, S			NO DEFORMATION ON CASE OR EXCESSIVE LOOSENESS OF THE TERMINALS			--	--
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, S.			SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.			--	--
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT				W Fukuchi	W Fukuchi	C. Harasumi	K. Katayama		
Unless otherwise specified, refer to MIL-STD-1344.				'99.11.12	'99.11.12	'99.11.12	'99.11.12		
Note QT: Qualification Test AT: Assurance Test X:Applicable Test									
HRS HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET			PART NO		
CODE NO (OLD)				DRAWING NO			PEART NO		
CL				ELC4 - 161021			CL541-0938-0		
							1/1		

TO