



Material

- ① Clamp: Brass, Ni plated
- ② Terminal screw: Steel Zinc plating "-" slot type
- ③ Wire guard solder pin: Brass, Tin plated
- ④ Terminal housing: Thermoplastic (UL94V-0), GREY

Electrical cULus

Voltage rating: 600V  
 Current rating: 65A  
 Wire range:  
 Solid wire (AWG): 6-22  
 Stranded wire (AWG): 6-22  
 Torque (Lb-In): 8.7 Lb-In  
 Screw: M4  
 Wire strip length: 6-7mm  
 Withstanding Voltage: 2.2KV  
 Operating temperature: -40°C to +115°C  
 Soldering temperature: 250°C ± 10°C / 5 Sec  
 Safety Approval: cULus

RoHS compliant



Scale	1:1					Date	Name	Customer-No.
TOLERANCE					Drawn	16.12.2010	Schulz	
X.	±0.50				Approved	16.12.2010	Gerber	ASSMANN WSW-No. A-TB000-V404
X.X	±0.30							Drawing-No.
X.XX	±0.10							ASS 4115C CO rev01
DIM	TOL	①	UL Update	23.03.2017	C.Bakula			Replace
X.°	±1°	②	Drawn	16.12.2010	Schulz			Sheet
Angle	TOL	Id.	Modification	Date	Name			