

**ConnectPower**  
**CP-BBU 115-230VAC / 24VDC****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com



UPS control modules provide the installation with a 12/24 V DC supply voltage within seconds should the power supply fail. Professional signalling guarantees the evaluation of all relevant signal conditions directly on site: the battery module performs the complete management of the external lead-acid accumulators. A constant charging and discharging routine guarantees a long service life for the batteries.

**General ordering data**

Order No.	<a href="#">9916280024</a>
Type	CP-BBU 115-230VAC / 24VDC
Version	UPS control unit, 24 V
GTIN (EAN)	4032248217878
Qty.	1 pc(s).

**ConnectPower**  
**CP-BBU 115-230VAC / 24VDC**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

**Technical data**
**Dimensions**

Length	161 mm	Width	72.5 mm
Height	127.5 mm	Weight	950 g

**Temperatures**

Operating temperature	-20 °C...+50 °C	Storage temperature	-20 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

**Input**

Conductor connection system	Screw connection	Connection range	AWG26-12 (0.1-4.0 mm <sup>2</sup> )
Input current	1 A @ 115 V AC; 0.6 A @ 230 V AC	Input frequency	50/ 60 Hz
Input fuse	2 A time-lag fuse (internal)	Input voltage (voltage mode input)	85...265 V AC; 120...300 V DC; typ. 115-230 V AC ±10%
Surge protection	Varistor	Turn-on current limit	Thermistor

**output**

Battery charging current	2 A	Battery voltage	27.3 V
Conductor connection system	Screw connection	Connection range	AWG26-12 (0.1-4.0 mm <sup>2</sup> )
Control at input voltage	0.2 %	Mains failure bridge-over time for 115 V AC	24 ms
Mains failure bridge-over time for 230 V AC	190 ms	Max. residual ripple	< 50 mV <sub>eff</sub>
Output current	Max. 15 A / max 9.0 A for power supply unit	Output voltage	24 V DC
output power	360 W		

**General data**

Degree of efficiency at max. load	72 %	Depth	127.5 mm
EMC standards	EN 55011, EN 55022, EN 55024, EN 61000-6-2, 3	Low Voltage Directive	73/ 23/ EWG
Operating temperature	-20 °C...+50 °C	Standards	DIN EN 50178, DIN EN 60950, IEC950
Status indication	Green LED (full charge): battery voltage > 29.5 V DC, Yellow LED (low battery): battery voltage < 22 V DC, Yellow LED (charging): BBU is loading battery, Red LED (error): no AC input voltage, Red LED (reversed battery): battery poles are reversed, LED red (battery open): no battery is connected	Switching frequency	100 kHz

**Insulation coordination**

Humidity at operating temperature	20 - 85% RH without condensation	Humidity at storage temperature	20 to 90%
Protection degree	IP 20	electrical isolation, I/O rail	3 kV
electrical isolation, input-earth	1.5 kV	electrical isolation, input-output	3 kV
electrical isolation, output-earth	0.5 kV		

**ConnectPower  
CP-BBU 115-230VAC / 24VDC**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Technical data****Classifications**

ETIM 2.0	EC001039	ETIM 3.0	EC001039
ETIM 4.0	EC002541	UNSPSC	30-21-18-01
eClass 4.1	27-24-04-10	eClass 5.1	27-04-90-02
eClass 6.0	EC27049201		

**Approvals**

Approvals



**ConnectPower**  
**CP-BBU 115-230VAC / 24VDC**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Electric symbol**

