

| | | | | |
|----------------------------|-----------------------------|--------------------------|---------------------------|--------------------------|
| APPLICABLE STANDARD | | | | |
| RATING | OPERATING TEMPERATURE RANGE | -35°C TO +85°C (NOTES 1) | STORAGE TEMPERATURE RANGE | -10°C TO + 60°C |
| | VOLTAGE | 50V AC | APPLICABLE CONNECTOR | DF17# (**)-*DP-0.5V (57) |
| | CURRENT | 0.3A | | |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|---------------------|---------------------------------------|-----------------------|----|----|
| CONSTRUCTION | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | X | X |

| ELECTRIC CHARACTERISTICS | | | | |
|---------------------------------|-------------------------|----------------------------|---|---|
| CONTACT RESISTANCE | 100m A (DC OR 1000 Hz). | 60mΩ MAX. | X | - |
| INSULATION RESISTANCE | 100V DC. | 500MΩ MIN. | X | - |
| VOLTAGE PROOF | 150V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | X | - |

| MECHANICAL CHARACTERISTICS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------------------|--|---|--------|------------------------|-------------------------|----|------|-----|----|------|-----|----|------|-----|----|------|-----|----|------|-----|----|------|-----|----|------|-----|----|------|-----|-----|-------|------|-----|-------|------|---|---|
| INSERTION AND WITHDRAWAL FORCES | MEASURED BY APPLICABLE CONNECTOR. | <table border="1" style="font-size: small;"> <thead> <tr> <th>SIGNAL</th> <th>INSERTION FORCE (N)MAX</th> <th>WITHDRAWAL FORCE (N)MIN</th> </tr> </thead> <tbody> <tr><td>20</td><td>20.0</td><td>2.0</td></tr> <tr><td>26</td><td>26.0</td><td>2.6</td></tr> <tr><td>30</td><td>30.0</td><td>3.0</td></tr> <tr><td>40</td><td>40.0</td><td>4.0</td></tr> <tr><td>50</td><td>50.0</td><td>5.0</td></tr> <tr><td>60</td><td>60.0</td><td>6.0</td></tr> <tr><td>70</td><td>70.0</td><td>7.0</td></tr> <tr><td>80</td><td>80.0</td><td>8.0</td></tr> <tr><td>100</td><td>100.0</td><td>10.0</td></tr> <tr><td>120</td><td>120.0</td><td>12.0</td></tr> </tbody> </table> | SIGNAL | INSERTION FORCE (N)MAX | WITHDRAWAL FORCE (N)MIN | 20 | 20.0 | 2.0 | 26 | 26.0 | 2.6 | 30 | 30.0 | 3.0 | 40 | 40.0 | 4.0 | 50 | 50.0 | 5.0 | 60 | 60.0 | 6.0 | 70 | 70.0 | 7.0 | 80 | 80.0 | 8.0 | 100 | 100.0 | 10.0 | 120 | 120.0 | 12.0 | X | - |
| SIGNAL | INSERTION FORCE (N)MAX | WITHDRAWAL FORCE (N)MIN | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 20.0 | 2.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 26 | 26.0 | 2.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30 | 30.0 | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 40 | 40.0 | 4.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50 | 50.0 | 5.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 60 | 60.0 | 6.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 70 | 70.0 | 7.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 80 | 80.0 | 8.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | 100.0 | 10.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | 120.0 | 12.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MECHANICAL OPERATION | 50TIMES INSERTIONS AND EXTRACTATIONS. | ① CONTACT RESISTANCE: 60mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| VIBRATION | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SHOCK | 490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| ENVIRONMENTAL CHARACTERISTICS | | | | |
|--------------------------------------|---|--|---|---|
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55→ 5 TO 35→ 85→ 5 TO 35°C TIME 30→10 TO 15→ 30→10TO15min UNDER 5 CYCLES. | ① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h. | ① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| CORROSION SALT MIST | EXPOSED IN 5% SALT WATER SPRAY FOR 48 h. | ① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION. | X | - |
| SULPHUR DIOXIDE | EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JEIDA-39) | ① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION. | X | - |
| HEAT RESISTANCE OF SOLDERING | [RECOMMENDED TEMPERATURE PROFILE] 《SOLDERING AREA》 MAX250°C, 220°C FOR 60 SECONDS MAX. 《PREHEATING AREA》 150 TO 180°C 90~120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. [RECOMMENDED MANUAL SOLDELING CONDITION] SOLDERING IRON TEMPERATURE 350°C SOLDERING TIME : WITHIN 3 SECONDS. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | X | - |

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|-------|--------------------------|----------|---------|------|
| △ | | | | |

| | | | |
|--|----------|---------------|----------|
| REMARKS NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT. UNLESS OTHERWISE SPECIFIED,REFER TO JIS C 5402. | APPROVED | KH. IKEDA | 05.08.26 |
| | CHECKED | AR. TAKAHASHI | 05.08.26 |
| | DESIGNED | YH. MICHIDA | 05.08.24 |
| | DRAWN | YH. MICHIDA | 05.08.24 |

| | | |
|--|-------------|-----------------------|
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | DRAWING NO. | ELC4-162129-07 |
|--|-------------|-----------------------|

| | | | | |
|----------------------------------|--|----------|---------------------------|-------|
| SPECIFICATION SHEET | | PART NO. | DF17B (3.0)-*DS-0.5V (57) | |
| HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL683 | △ 1/1 |