



NOTE 1. NO PLATING ON THE SHEARED EDGES OF CONTACT.
 NOTE 2. CRIMP TYPE ARE MARKED AS INDICATED.

TABLE 1

CRIMP TYPE	APPLICABLE WIRE		DIMENSIONS			
	WIRE SIZE	INSULATION OUTER DIA.	A	B	C	D
C 1	AWG#18~22 (0.8mm~0.3mm)	ϕ 2.3MAX.	28.43	5.81	3.92	2.49
C 2	AWG#22~26 (0.3mm~0.13mm)	ϕ 1.0~ ϕ 1.7	29.04	6.42	4.53	2.7

1	#20PIN CONTACT	1	COPPER ALLOY	SILVER PLATING				
ITEM	DESCRIPTION	Q'TY	MATERIAL	FINISH	REMARKS			
UNLESS OTHERWISE SPECIFIED: T700142		DATE	TITLE					
DIMENSIONS ARE IN MILLIMETERS TOLERANCES ON : (INCHES)		13. Mar. '95	JAE-CONNECTOR.COM Reference Only ST-JL05-20P-C (#20PIN CONTACT) (INDIVIDUAL)					
		DRAWN				JAPAN INJECTION ELECTRONICS INDUSTRY, LTD.		
		S. NANA O				MUSASHINO, AKISHIMA-SHI TOKYO, JAPAN		
		CHECKED				DWG. NO.		
		T. MORITA						
		APP'D	SERIES					
		M. Takagi	JL05					
		APP'D	SCALE					
			3/1					
			S J 0 2 5 4 2 0 - E					