


RECOMMEND P.C.B. LAYOUT



CIRCUIT: DPDT  
CONTACT CONFIGURATION

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
<DN>	OFF	<DN>
2-3, 5-6	DPEN	2-1, 5-4

( ) =Momentary

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: 0.0±0.4  
0.00±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. CONTACT RATING: 5 Amps @120VAC or 28VDC; 2 Amps @250VAC.
  5. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
  6. INSULATION RESISTANCE: 1,000M Ohms min.
  7. DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
  8. OPERATING TEMP.: -30°C to 85°C

B	16101	UPDATE TITLE	6/8/06	CT
A	10455	RELEASED FOR PRODUCTION		
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE		DATE	DR	DWG	REV
300DP4J3BLKVS2QE		1.5:1		12/7/99	MM	T3224004	B

**E-SWITCH®**

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED