

Specification Sheet

Part Number: CTP580



Convoluted Tubing, Slit, .63" Dia, PE, Black, 5500 ft/carton

Article Number

169-60516

Type

CTP580

Color

Black (BK)

Features & Benefits

- Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.
- Tubing provides full coverage where spiral wrap or other coverings may not be suitable.
- In harsh applications the tubing provides resistance to crushing, impact, and abrasion.
- Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Quantity Per

carton

Product Description

HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description

Convoluted Tubing, Slit, .63" Dia, PE, Black, 5500 ft/carton

Global Part Name

CTP580-PE-BK

Technical Description

Convoluted Tubing, Slit, 5/8" Dia., PE, Black

Length L (Imperial)

5500.0

Length L (Metric)

1676.4

Inner Diameter D (Imperial)

0.639

Inner Diameter D (Metric)

16.23

Diameter D (imperial)

0.837

Diameter D (metric)

21.26

Outside Diameter OD(Imperial)

0.837

Outside Diameter OD(metric)

21.26

Nominal Diameter (Imperial)

0.625

Nominal Diameter (Metric)

15.88

Wall Thickness WT (Imperial)	.005
Wall Thickness WT (Metric)	0.127
Material	Polyethylene (PE)
Material Shortcut	PE
Halogen free	No
Operating Temperature (Metric)	-40°F to +199°F (-40°C to +93°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	5500
Package Quantity (Metric)	1676.40
Customs Number	3926909987