



PC board drilling dimensions  
(after plating – thickness: 1.60 to 3.20 mm)

LEAD FREE PART NUMBER

PART NUMBER	
flash gold	D50P91C4P*00LF
0.76µ gold	D50P91C6P*00LF

Threaded ØT M3 = L  
Threaded ØT 4.40 = X

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:  
SEE DRAWING C01-8646-0001

Notes:

1) The nut can protrude above the surface of insulator but maintaining the footprint dimension 6.0±0.15 mm.

mat'l. code		surface		tolerance		projection		product family	
-		ISO 1302 ✓		ISO 406 ISO 1101				D-SUB	
ltr	ecn no	dr	date	tolerances unless otherwise specified				title	
E	ELX-I-22878	AB	2015/01/06	angles	linear	MM		MALE CONNECTOR DELTA-D STRAIGHT – PRESS FIT	
				0°±2'		scale 2:1		dwg no	
				dr	PESSON	1996/07/24			sheet 1 of 1
				enr	ALIAS BABU	2015/01/06	C01-8646-0463		A3
				chr	MITHUN PAUL	2015/01/06	type		Product Customer Drawing
				app	BIJU K PAUL	2015/01/06			
sheet index	revision sheet	E	1						