

Specification Sheet

Part Number: 155-05800



1-Piece Cable Tie/Fir Tree Mount With Disc, 6.0"L, .26"-.28" Mounting Hole, PA66HIRHS, Black, 1,500/pkg

Article Number	155-05800
Type	T50SOSFT6E
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.• Initial fir tree serves as a locating feature for assistance in blind assembly applications.• Disc feature provides anti-rattle protection in high vibration applications.
Quantity Per	bag
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force.
Short Description	1-Piece Cable Tie/Fir Tree Mount With Disc, 6.0"L, .26"-.28" Mounting Hole, PA66HIRHS, Black, 1,500/pkg

Global Part Name

T50SOSFT6E-PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

150

Length L (Imperial)

6.0

Length L (Metric)

160

Fixation Method

Fir Tree

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.19

Width W (Metric)

4.7

Bundle Diameter Min (Imperial)

0.04

Bundle Diameter Min (Metric)

1.6

Bundle Diameter Max (Imperial)

1.4

Bundle Diameter Max (Metric)

32.0

Thickness T (Imperial)

0.05

Thickness T (Metric)	1.35
Height H (Imperial)	0.33
Panel Thickness Min(Imperial)	0.03
Panel Thickness Max(Imperial)	0.12
Panel Thickness Min (Metric)	0.75
Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.26 - 0.28
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.26
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 1500

Package Quantity (Metric) 1500

Customs Number 3926909987

Content Unit(BMEcat) pcs.

Weight (Metric) 2.0