

MPC5775B/E Microcontrollers

Ultra-Reliable MCUs Built on Power Architecture® Technology

Product One-Sheet

Multicore Performance – High performance and integration for motor control and battery management.

Advanced Timers and ADCs – Programmable motor control timer (eTPU) and Sigma-Delta ADC converters on the MPC5775E MCU allow for advanced motor control and implementation of a software resolver without expensive external components.

Quality, Security and Redundancy – AEC-Q100 qualification testing, on-chip security encryption protection using CSE and TDM for tamper proofing, and lockstep cores help support ASIL-D and SIL-1 functional safety (ISO26262/ IEC61508) requirements.

MPC5775B/E Specifications


Feature	MPC5775B	MPC5775E
Flash	4 MB	4 MB
RAM	512 KB	512 KB
Cores	2x z7 (1 in LS)	2 x z7 (1 in LS)
Speed	220 MHz	264 MHz
Timer/PWM	2 x eMIOS, 32-ch. total	2 x eMIOS, 32-ch. total 3 x eTPU, 96-ch. total
Analog	2 x eQADC, 40-ch. total	4 x eQADC, 70-ch. total 4 x SD ADC, 20-ch. total
Ethernet	1 x FEC Module	1 x FEC Module
SCI/SPI	5/5	5/5
CAN	2x MCAN-FD, 4x FlexCAN	2x MCAN-FD, 4x FlexCAN
Security	Hardware CSE module	Hardware CSE module
Op Range	3.0 V – 5.5 V	3.0 V – 5.5 V
Temp (Ta)	-40°C to 125°C	-40°C to 125°C
Package	416 BGA	416 BGA

www.nxp.com/MPC5775BE


NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org. All rights reserved. © 2018 NXP B.V.

Document Number: MPC5775BEFS REV 0

MPC5775B Block Diagram



MPC5775E Block Diagram



Target Applications

- Hybrid and Electric Traction Motors
- Battery Management Systems (BMS)
- Engine Control Units (ECU)
- Safety Critical Applications

Enablement Tools

- Evaluation boards:
 - MPC5775BE-416DS
 - MPC57XXXMB motherboard
- S32 Design Studio (S32DS)
- NVM/flash drivers
- AUTOSAR MCAL drivers (SDK)
- Green Hills®, Wind River® (Diab)
- Lauterbach
- iSystem
- P&E Micro, ETAS and PLS

Orderable Samples

Part Number	Temp Range (Ta)	Package
SPC5775BDK3MME2	-40 to 125 °C	416-pin MAPBGA
SPC5775EDK3MME3	-40 to 125 °C	416-pin MAPBGA

