


RECOMMEND PANEL LAYOUT



CIRCUIT: DP (90° INDEXING)
CONTACT CONFIGURATION

SWITCH FUNCTION	
CONNECTED TERMINAL #	POS. #
8-1, 4-5	1-3, 5-7

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. CONTACT RATING: 4A @125VAC/28VDC, 2A @250VAC
 5. CONTACT RESISTANCE: Below 10 milliohms
 6. DIELECTRIC STRENGTH: 1KV RMS min. at sea level
 7. ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.
 8. LOCK: bright nickel plated zinc alloy with nickel facing (black and polished chrome facing available)
 9. Tumbler mechanism: 4-disc tumbler
 10. KEYS: Nickel plated with code no. A126 (2 Keys)
 11. CONTACTS: silver plated Cu (Q contact material)
 12. TERMINALS: silver plated Cu (Q contact material)
 13. CONTACT SPRING: piano wire
 14. MOUNTING NUT: nickel plated zinc alloy



REV.	ECN NO.	DESCRIPTION	DATE	CHK'D
A	10471	RELEASED FOR PRODUCTION		

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

TITLE	SCALE	DATE	DR	DWG	REV
KD130S (Key Code No. A126)	1.5:1	10/5/01	CB	K200228	A