

**CWDM305PD****SURFACE MOUNT SILICON  
DUAL P-CHANNEL  
ENHANCEMENT-MODE  
MOSFET****SOIC-8 CASE**[www.centrasemi.com](http://www.centrasemi.com)**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CWDM305PD is a dual high current P-channel enhancement-mode silicon MOSFET manufactured by the P-channel DMOS process, and is designed for high speed pulsed amplifier and driver applications. This MOSFET offers high current, low  $r_{DS(ON)}$ , low threshold voltage, and low gate charge.

**MARKING CODE: C503****APPLICATIONS:**

- Load/Power switches
- Power supply converter circuits
- Battery powered portable equipment

**FEATURES:**

- Low  $r_{DS(ON)}$  (83m $\Omega$  MAX @  $V_{GS}=5.0V$ )
- High current ( $I_D=5.3A$ )

**MAXIMUM RATINGS:** ( $T_A=25^\circ C$ )

Drain-Source Voltage
Gate-Source Voltage
Continuous Drain Current (Steady State)
Maximum Pulsed Drain Current, $t_p=10\mu s$
Power Dissipation
Operating and Storage Junction Temperature
Thermal Resistance

SYMBOL		UNITS
$V_{DS}$	30	V
$V_{GS}$	16	V
$I_D$	5.3	A
$I_{DM}$	21.2	A
$P_D$	2.0	W
$T_J, T_{stg}$	-55 to +150	$^\circ C$
$\theta_{JA}$	62.5	$^\circ C/W$

**ELECTRICAL CHARACTERISTICS PER TRANSISTOR:** ( $T_A=25^\circ C$  unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
$I_{GSSF}, I_{GSSR}$	$V_{GS}=20V, V_{DS}=0$			100	nA
$I_{DSS}$	$V_{DS}=30V, V_{GS}=0$			1.0	$\mu A$
$BV_{DSS}$	$V_{GS}=0, I_D=250\mu A$	30			V
$V_{GS(th)}$	$V_{GS}=V_{DS}, I_D=250\mu A$	1.0		3.0	V
$r_{DS(ON)}$	$V_{GS}=10V, I_D=2.7A$		0.066	0.072	$\Omega$
$r_{DS(ON)}$	$V_{GS}=5.0V, I_D=2.7A$		0.077	0.083	$\Omega$
$g_{FS}$	$V_{DS}=5.0V, I_D=5.3A$		11		S
$C_{rSS}$	$V_{DS}=10V, V_{GS}=0, f=1.0MHz$		50	60	pF
$C_{iSS}$	$V_{DS}=10V, V_{GS}=0, f=1.0MHz$		500	590	pF
$C_{oss}$	$V_{DS}=10V, V_{GS}=0, f=1.0MHz$		60	150	pF
$Q_{g(tot)}$	$V_{DD}=15V, V_{GS}=5.0V, I_D=5.3A$		4.7	7.0	nC
$Q_{gs}$	$V_{DD}=15V, V_{GS}=5.0V, I_D=5.3A$		1.4	2.1	nC
$Q_{gd}$	$V_{DD}=15V, V_{GS}=5.0V, I_D=5.3A$		1.7	2.5	nC
$t_{on}$	$V_{DD}=15V, I_D=5.3A, R_G=10\Omega$		7.0		ns
$t_{off}$	$V_{DD}=15V, I_D=5.3A, R_G=10\Omega$		8.0		ns


R3 (10-August 2018)

CWDM305PD

**SURFACE MOUNT SILICON  
DUAL P-CHANNEL  
ENHANCEMENT-MODE  
MOSFET**




**SOIC-8 CASE - MECHANICAL OUTLINE**



SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.055	0.061	1.392	1.554
B	0.004	0.009	0.100	0.224
C	0.016	0.035	0.40	0.90
D	0.007	0.010	0.19	0.25
E	0.145	0.157	3.80	4.00
F	0.189	0.198	4.80	5.00
G	0.150		3.81	
H	0.228	0.244	5.80	6.20
J	0.013	0.020	0.33	0.51
K	0.050		1.27	

SOIC-8 (REV: R1)

**PIN CONFIGURATION**




**LEAD CODE:**

- 1) Source Q1      5) Drain Q2
- 2) Gate Q1        6) Drain Q2
- 3) Source Q2      7) Drain Q1
- 4) Gate Q2        8) Drain Q1

**MARKING CODE: C503**

**SUGGESTED MOUNTING PADS**

(Dimensions in mm)



R3 (10-August 2018)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)