

BCH-508H- 6 BK VPE500 - 5441692

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 12 A, Color: black, Contact surface: Tin, Mounting: Wave soldering



Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Minimum order quantity | 500 pc |
| Weight per Piece (excluding packing) | 2.08 g |
| Custom tariff number | 85366990 |
| Country of origin | China |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

Approvals

Approvals

Approvals

VDE Gutachten mit Fertigungsüberwachung / IECCEB Scheme / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

BCH-508H- 6 BK VPE500 - 5441692


Approvals

Approvals submitted


Approval details

VDE Gutachten mit Fertigungsüberwachung 

IECEE CB Scheme 

UL Recognized 

| | B | D |
|--------------------------------|-------|-------|
| Nominal current I _N | 15 A | 15 A |
| Nominal voltage U _N | 300 V | 150 V |

cUL Recognized 

| | B | D |
|--------------------------------|-------|-------|
| Nominal current I _N | 15 A | 15 A |
| Nominal voltage U _N | 300 V | 150 V |

cULus Recognized 