

**WR/PG16-50M**

Order No.: 1666841

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1666841>Corrugated tube, for corrugated tube screw connection, packing  
volume 50 m, size Pg16**Commercial data**

EAN	4017918136888
Pack	1 pcs.
Customs tariff	39173900
Weight/Piece	1.494 KG
Catalog page information	Page 556 (PC-2009)

**Product notes**WEEE/RoHS-compliant since:  
01/01/2003


<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****General data**

Pg screw connection	16
Material	PA
Inflammability class acc. to UL 94	HB
Ambient temperature (operation)	-40 °C ... 110 °C

## Diagrams/Drawings

### Dimensioned drawing



### Assembly instructions for Pg16 corrugated pipe

a = Corrugated screw connection

B = Corrugated pipe

c = Opener

#### Installation note:

Cut the corrugated pipe in the groove to retain a round shape for insertion. The lighter seal (not depicted in the illustration) is positioned in the corrugated pipe screw connection below the safety latch. The darker outer seal (not depicted in the illustration) is placed over the corrugated pipe screw connection from outside. The corrugated pipe is then pushed as far as possible into the corrugated pipe screw connection and clicks into place. The screw connection is opened by placing the yellow corrugated pipe opener with force between the safety latch and the corrugated tube and the corrugated pipe is then pulled out.

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;