

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

| LOC | DIST | REVISIONS | | | |
|-----|------|-------------|------|-----|------|
| P | LTR | DESCRIPTION | DATE | DWN | APVD |
| CE | 16 | SEE SHEET 1 | | | |

| MAX IL (dB) | L METERS [INCHES] | PART NUMBER |
|-------------|------------------------------|-------------|
| 0.68 | 50.000±0.500 [1968.5±19.69] | 5-1938209-0 |
| 0.64 | 40.000±0.400 [1574.80±15.75] | 4-1938209-0 |
| 0.64 | 39.000±0.390 [1535.43±15.35] | 3-1938209-9 |
| 0.63 | 38.000±0.380 [1496.06±14.96] | 3-1938209-8 |
| 0.63 | 37.000±0.370 [1456.69±14.57] | 3-1938209-7 |
| 0.63 | 36.000±0.360 [1417.32±14.17] | 3-1938209-6 |
| 0.62 | 35.000±0.350 [1377.95±13.78] | 3-1938209-5 |
| 0.62 | 34.000±0.340 [1338.58±13.39] | 3-1938209-4 |
| 0.62 | 33.000±0.330 [1299.21±12.99] | 3-1938209-3 |
| 0.61 | 32.000±0.320 [1259.84±12.60] | 3-1938209-2 |
| 0.61 | 31.000±0.310 [1220.47±12.20] | 3-1938209-1 |
| 0.61 | 30.000±0.300 [1181.10±11.81] | 3-1938209-0 |
| 0.60 | 29.000±0.290 [1141.73±11.42] | 2-1938209-9 |
| 0.60 | 28.000±0.280 [1102.36±11.02] | 2-1938209-8 |
| 0.59 | 27.000±0.270 [1062.99±10.63] | 2-1938209-7 |
| 0.59 | 26.000±0.260 [1023.62±10.24] | 2-1938209-6 |
| 0.59 | 25.000±0.250 [984.25±9.84] | 2-1938209-5 |
| 0.58 | 24.000±0.240 [944.88±9.45] | 2-1938209-4 |
| 0.58 | 23.000±0.230 [905.51±9.06] | 2-1938209-3 |
| 0.58 | 22.000±0.220 [866.14±8.66] | 2-1938209-2 |
| 0.57 | 21.000±0.210 [826.77±8.27] | 2-1938209-1 |
| 0.57 | 20.000±0.200 [787.40±7.87] | 2-1938209-0 |
| 0.57 | 19.000±0.190 [748.03±7.48] | 1-1938209-9 |
| 0.56 | 18.000±0.180 [708.66±7.09] | 1-1938209-8 |
| 0.56 | 17.000±0.170 [669.29±6.69] | 1-1938209-7 |
| 0.56 | 16.000±0.160 [629.92±6.30] | 1-1938209-6 |
| 0.55 | 15.000±0.150 [590.55±5.91] | 1-1938209-5 |
| 0.55 | 14.000±0.150 [551.18±5.91] | 1-1938209-4 |
| 0.55 | 13.000±0.150 [511.81±5.91] | 1-1938209-3 |
| 0.54 | 12.000±0.150 [472.44±5.91] | 1-1938209-2 |
| 0.54 | 11.000±0.150 [433.07±5.91] | 1-1938209-1 |
| 0.54 | 10.000±0.150 [393.70±5.91] | 1-1938209-0 |
| 0.53 | 9.000±0.150 [354.33±5.91] | 1938209-9 |
| 0.53 | 8.000±0.080 [314.96±3.15] | 1938209-8 |
| 0.52 | 7.000±0.080 [275.59±3.15] | 1938209-7 |
| 0.52 | 6.000±0.080 [236.22±3.15] | 1938209-6 |
| 0.52 | 5.000±0.080 [196.85±3.15] | 1938209-5 |
| 0.51 | 4.000±0.080 [157.48±3.15] | 1938209-4 |
| 0.51 | 3.000±0.050 [118.11±1.97] | 1938209-3 |
| 0.51 | 2.000±0.050 [78.74±1.97] | 1938209-2 |
| 0.50 | 1.000±0.050 [39.37±1.97] | 1938209-1 |

| MAX IL (dB) | L METERS [INCHES] | PART NUMBER |
|-------------|-------------------|-------------|
|-------------|-------------------|-------------|

| | | | | |
|---|-------------|----------------------------------|---|-----------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN K.GLATFELTER 14JAN2009 | Tyco Electronics Corporation Harrisburg, PA 17105-3608 | |
| DIMENSIONS: METERS [INCHES] | | CHK J.BARRY | NAME CABLE ASSEMBLY, FIBER OPTIC, 50/125um 3mm ROUND CABLE, OFNP, MPO W/NO PINS, REVERSED PATH | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD J.BARRY | SIZE A2 | |
| 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± - | | PRODUCT SPEC - | CAGE CODE 00779 | DRAWING NO 1938209 |
| MATERIAL - | FINISH - | APPLICATION SPEC - | RESTRICTED TO - | SCALE NTS |
| CUSTOMER DRAWING | | | SHEET 2 OF 2 | REV A |